



Permatex®

EPOXY SERIES

TOUGH BONDS FOR TOUGH JOBS

Permatex® epoxies deliver a long lasting bond for all your automotive and household needs.



NEW GEL EPOXY
No drip. No mess. No waste.



GEL EPOXY

No drip. No mess. No waste.

Permatex® Gel Epoxies revolutionize the traditional epoxy experience, delivering a noticeable improvement to the typical repair process. Its thicker, no drip gel formula means your repair is completed with no mess and no clamping. Permatex® Gel Epoxies are infused with a blue dye which disappears when the product is perfectly mixed – taking the guesswork out of when to apply it.



1 Minute Epoxy

2500 PSI SHEAR STRENGTH

Permatex® General Purpose 1 Minute Epoxy is a fast setting, high strength two-part adhesive and filler system specially formulated with a Blue Dye Indicator that disappears when it's fully mixed and ready to use. The no drip gel formula ensures that each repair is completed with no mess and no clamping.

- General Purpose
- No clamp, no drip gel
- Blue dye disappears when mixed

BONDS TO:

Metals, Hard Plastics, Ceramics, Glass, Rubber and more!

Set Time: 1 min. Cure Time: 5 min. Finished Color: Clear

Item # 84160



5 Minute Epoxy

3400 PSI SHEAR STRENGTH

Permatex® General Purpose 5 Minute bonds to surfaces with the flexibility to reposition before the setting time. The Blue Dye disappears indicating when it's fully mixed and ready to use. The no drip gel formula ensures that each repair is completed with no mess and no clamping.

- General Purpose
- No clamp, no drip gel
- Blue dye disappears when mixed

BONDS TO:

Metals, Hard Plastics, Ceramics, Glass, Rubber and more!

Set Time: 5 min. Cure Time: 10 min. Finished Color: Clear

Item # 84101

ITEM	DESCRIPTION	CASE QTY	CASE L"	CASE W"	CASE H"	CASE CUBE	UPC PREFIX 0686226
84160	Permatex® 1 Minute Epoxy Gel, 25mL	6	9	8.5	5	0.232	84160 5
84101	Permatex® 5 Minute Epoxy Gel, 25mL	6	9	8.5	5	0.232	84101 8



500° High Heat Epoxy

2500 PSI SHEAR STRENGTH

Permatex® High Heat Epoxy is the only liquid epoxy available in a standard 2-part syringe that can withstand intermittent temperatures up to 500°F.

- Resists temperatures up to 500°F
- Underhood and automotive applications
- Chemical resistant

BONDS TO:

Metals, Hard Plastics, Ceramics, Glass, Rubber and more!

Set Time: 10 min. Cure Time: 2 hr. Finished Color: Amber

Item # 84102



2 Ton Epoxy

4000 PSI SHEAR STRENGTH

Permatex® Clear 2 Ton Epoxy is a general-purpose high strength epoxy designed to bond together rigid materials for a permanent hold.

- High -strength
- Fills gaps and will not shrink
- Long set time for multiple repairs

BONDS TO:

Ceramics, Fibreglass, Metal, Concrete and more!

Set Time: 30 min. Cure Time: 1 hr. Finished Color: Clear

Item # 84133



Marine H2 Hold Epoxy

4000 PSI SHEAR STRENGTH

Permatex® Marine H2 Epoxy bonds underwater without breaking. This industrial strength epoxy is ideal for portable water tanks, fuel tanks, drains, boats and other main components that are exposed to salt or fresh water.

- Flexible water-proof adhesive
- Sticks and cures underwater
- Shock & vibration resistant

BONDS TO:

Fibreglass, PVC, Metal, Wood, Plastics and more!

Set Time: 15 min. Cure Time: 1 hr. Finished Color: Off-white

Item # 84200

ITEM	DESCRIPTION	CASE QTY	CASE L"	CASE W"	CASE H"	CASE CUBE	UPC PREFIX 0686226
84102	Permatex® 500° High Heat Epoxy, 25mL	6	9	8.5	5	0.232	84102 5
84133	Permatex® 2 Ton Epoxy, 25mL	6	9	8.5	5	0.232	84133 9
84200	Permatex® Marine H2 Hold Epoxy, 25mL	6	9	8.5	5	0.232	84200 8

